

# MAK LOTEX GREASE A

## Description

MAK LOTEX GREASE A is an NLGI 2 calcium based water resistant grease containing bitumen

## Application

- This is recommended for roll neck bearings of metal rolling mills with centralized lubrication systems. It is also suitable for use in the presence of large quantity of water at temperatures up to 60°C

## Benefits

- Extreme pressure additive package, which ensures extended life to components subject to high loads, shock loads, extreme ambient temperatures and very dusty environment

## Performance Level

- Proprietary grade

## Technical Specifications

Characteristics	Test Method	MAK LOTEX A GREASE
Consistency of the Worked Grease at 25°C	ASTM D 217	295
Drop Point, °C	ASTM D 566	98
Copper Strip Corrosion Test @ 75°C for 24 hrs.	ASTM D 4048	Negative

All the mentioned values are typical which may vary from batch to batch.

## Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept vertically and should be kept away from dusty or heated areas.
- Lid should not be left open and during handling any contact with dust must be avoided
- Containers used for grease transport should be clean and exclusive

## Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred

## Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below

### **Bharat Petroleum Corporation Ltd.**

Product and Application Development Dept.  
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)  
 Mumbai -400015  
 E-mail: [MAKcustomercare2@bharatpetroleum.in](mailto:MAKcustomercare2@bharatpetroleum.in)  
 Tel No.: 022-24176351