

MAK CANE CRUSHING OIL NB 40

Description

This is non-bituminous oil blended from heavy-bodied base oils and contains selected non-toxic mild EP additives to ensure efficient lubrication of machine elements even in the presence of sugarcane juice

Application

These are exclusively developed to meet the requirements of heavily loaded, slow speed Mill Roll Bearings in Sugar Mills. Being non-bituminous in nature, it is easier to dispose off the used lubricant

Benefits

- Excellent lubrication
- Prevents wear and corrosion of bearings under all operating conditions
- Excellent resistance to leakage

Performance Level

- Proprietary grades

Technical Specifications

Characteristics	Test Method	MAK CANE CRUSHING OIL NB 40
Appearance	--	Dark brown
Density at 15°C	P:16	0.8986
K.V. at 100°C, cSt	ASTM D 445	39.71
Pour Point, °C	ASTM D 97	-6
Flash Point, (COC), °C	ASTM D 92	240
Copper Strip Corrosion Test at 100°C for 3 hrs.	ASTM D 130	1a

All the mentioned values are typical which may vary from batch to batch

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept vertically and should be kept away from dusty or heated areas
- Lid should not be left open and during handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
 Mumbai -400015
 E-mail: MAKcustomercare2@bharatpetroleum.in
 Tel No.: 022-24176351