

MAK TURGONA

Description

These are highly refined straight mineral oils with good oxidation stability.

Application

These are highly refined straight mineral oils with good oxidation stability.

Benefits

- Excellent oxidation stability

Performance Level

- Proprietary grades

Technical Specifications

Characteristics	ASTM	MAK TURGONA		
		30	40	50
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright
Density @15°C	D1298	0.8881	0.8919	0.8999
K.V at 100° C, cSt	D445	11.2	14.3	18.7
Viscosity Index	D2270	96	95	95
Pour Point, °C	D97	-9	-6	-6
Flash Point, (COC), °C	D92	230	242	254
Copper strip Corrosion @ 100 °C	D130	1a	1a	1a

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351