

MAK LITHUMOL J

Description

MAK LITHUMOL J oil is compounded type, high viscosity index mineral oil.

Application

Recommended for use in gear boxes where high viscosity and compounded type of oils are required.

Benefits

- High viscosity
- Good wettability and water replacement properties

PERFORMANCE LEVEL

- IS 1589 : 1994 (Type 2) [Reaffirmed March, 2001]

Our grades meet above specifications for the respective viscosity grades.

Technical Specifications

Characteristics	ASTM Test method	MAK LITHUMOL J
Appearance	--	Dark brown fluid
Density at 15° C	D1298	0.9096
K.V at 40° C, cSt	D445	680.2
Viscosity Index	D2270	90
Pour Point, °C	D97	-3
Flash Point, (COC), °C	D92	288
Copper Strip Corrosion Test at 100°C for 3 hrs.	D130	1a

All the mentioned values are typical which may vary from batch to batch

Storage and Handling

- Indoor Storage is always preferable
- Closed Barrels should be kept horizontally with bung position at 3'O Clock 9 'O Clock position
- Barrels should be kept away from dusty or heated areas as much as possible

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Advice

. For any further advice on applications or otherwise please contact the nearest Bharat Petroleum Territory Office or Technical Services Department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
 Mumbai -400015
 E-mail: MAKcustomercare2@bharatpetroleum.in
 Tel No.: 022-24176351