

MAK HYDROL TQ 32

Description

This is a specially developed hydraulic transmission fluid fortified with high performance additives that incorporates excellent properties for catering to the severe demands of gears and bearings in transmission.

Application

It is recommended for use in Turbo Transmission systems, Torque Converters & Fluid Couplings.

Benefits

- Good anti-wear and anti-rust properties
- Excellent extreme pressure properties
- Useful in low temperature operating conditions

Performance Level

- 3.90-8A of Voith Getriebe, Germany

Technical Specifications

Characteristics	ASTM	MAK HYDROL TQ 32
Density at 15° C	D1298	0.856
K.V at 40° C, cSt	D445	32.5
Viscosity Index	D2270	118
Pour Point, °C	D97	-45
Flash Point, (COC), °C	D92	234
TAN, mg KOH / g		0.22
Color No		L 0.5

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351