



MAK SPINDLE OIL 22

Description

MAK Spindle oil is blended from highly refined superior quality base oil and additives having high viscosity index, good oxidation stability, antifoam and providing a good film strength and resistance to rusting and corrosion. It provides excellent performance for lubrication of machine tools and other equipments, where low viscosity oils are required.

Application

Spindle bearings of textile machinery operating at low to medium speed.

Benefits

- Exceptionally good oxidation and thermal stability
- Non corrosive & non toxic
- Rust inhibition
- Provides Good film strength and antifoaming property

PERFORMANCE LEVEL

Proprietary grade

Technical Specifications

Characteristics	ASTM	MAK SPINDLE OIL 22
Appearance	--	clear brown fluid
Density at 15°C	D1296	0.908
K.V at 40° C, cSt	D445	22.1
Viscosity Index	D2270	100
Pour Point, °C	D97	-6
Flash Point, (COC), °C	D92	176

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bung position at 3'o'clock 9 'o clock position
- Barrels should be kept away from dusty or heated areas as much as possible
- During handling any contact with dust must be avoided.

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Advice

For any further advice on applications or otherwise please contact the nearest Bharat Petroleum Territory Office or Technical Services Department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351