



**MAK**<sup>®</sup>  
**LUBRICANTS**

# MAK TRANSMISSION FLUID F

## Description

MAK TRANSMISSION FLUID F is a premium quality transmission Fluid having a low coefficient of friction, fortified with additives to impart excellent thermo-oxidative stability, low temperature flow characteristic, seal compatibility, anti-wear and anti-corrosion properties. This oil ensures smooth operation with a minimum power loss.

## Application

Recommended for use in transmission systems requiring specific clutch and band frictional characteristic meeting Ford ESW-M2C-33F specifications and power Sheerings.

## Benefits

- Excellent frictional properties
- Outstanding low temperature fluidity
- Good seal compatibility

## PERFORMANCE LEVEL

- Ford ESW-M2C-33F

## Technical Specifications

Characteristics	ASTM	MAK TRANSFLUID F
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Brown
Density @15°C	D1298	0.8627
K.V at 100° C, cSt	D445	7.27
Viscosity Index	D2270	178
Flash Point, (COC), °C	D92	210
Pour Point, °C	D97	-42

All the mentioned values are typical which may vary from batch to batch.

## Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bung position at 3'o'clock 9 'o clock position
- Barrels should be kept away from dusty or heated areas as much as possible
- During handling any contact with dust must be avoided.

## Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

## Advice

For any further advice on applications or otherwise please contact the nearest Bharat Petroleum Territory Office or Technical Services Department at the address given below.

### **Bharat Petroleum Corporation Ltd.**

Product and Application Development Dept.  
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)  
Mumbai -400015  
E-mail: [MAKcustomercare2@bharatpetroleum.in](mailto:MAKcustomercare2@bharatpetroleum.in)  
Tel No.: 022-24176351