

MAK RUSTROL 152

It is oil based rust preventive fluid, which forms thin, tenacious oily film on the surface of the metal to be protected. The protected components can be furthered processed without the removal of this oil.

This grade is applied for protecting steel sheets and strips, metal stacks during the inter process storage period.
This grade is applied by dip or swab method.

- Contains corrosion inhibitors
- The product is compatible with general lubricating oils

- Proprietary grade



Characteristics	IS 1448	Typical Figures
Appearance	--	Light brown clear fluid
Density at 15°C	P:16	0.9146
K.V at 40° C, cSt	P:25	35.71
Viscosity Index	P:56	102
Pour point, °C	P:10	3
Flash Point, (Abel), °C	P:69	200
Copper corrosion @ 100°C for 3 hrs.	P:15	1a

All the mentioned values are typical which may vary from batch to batch.



- Indoor Storage is always preferable
- Barrels should be kept vertically and should be kept away from dusty or heated areas.
- Lid should not be left open and during handling any contact with dust must be avoided



This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.



For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351